



12 Circulation Pumps

Albin Group's a series of DC-driven Circulation Pumps are designed for circulation of water/antifreeze in heating or cooling systems on boats, buses, motorhomes. and commercial vehicles.

DC driven Circulation Pumps with Brushless Motor..... 129

albinus[®]

12V or 24V DC driven Circulation Pumps with Brushless Motor. Pumps for the circulation of water/antifreeze in heating or cooling systems on boats, buses, motor homes and commercial vehicles.

- Small size with high efficiency, maintenance-free
- Ceramic Shaft and Carbon fiber sleeve
- Completely water proof (IP68)
- Brushless DC control, long service life.
- Motor Brushless magnetic isolated design
- For Continuous Duty
- Life span 20 000 hours
- Materials of pump housing ABS, PES/SPS/PA66
- Noise class 35dB
- Max. Liquid Temp.: Continuous Duty + 80°C, Intermittent + 100°C.

BL10CM 12V / 24V

SKU	Type	Voltage	Capacity at 0.1 bar	Capacity at 0.25 bar	Max. Power Consumption	Port size	Dimensions HxWxL	Weight
13-01-005	DC driven Circulation Pumps with Brushless Motor	12V	19 l/min 301 GPH	16 l/min 254 GPH	80W	14 mm (5/8")	76x68x89 mm (3.0x2.7x3.5 in)	0.2 kg 0.44 lb
13-01-006		24V	21 l/min 333 GPH	18 l/min 285 GPH	40W			



BL30CM 12V / 24V

SKU	Type	Voltage	Capacity at 0.1 bar	Capacity at 0.25 bar	Max. Power Consumption	Port size	Dimensions HxWxL	Weight
13-01-001	DC driven Circulation Pumps with Brushless Motor	12V	32 l/min 507 GPH	28 l/min 444 GPH	54W	20 mm (3/4")	99x83x113 mm (3.9x3.3x4.5 in)	0.48 kg 1.1 lb
13-01-002		24V	38 l/min 602 GPH	36 l/min 571 GPH	80W			



BL90CM 12V / 24V

SKU	Type	Voltage	Capacity at 0.1 bar	Capacity at 0.25 bar	Max. Power Consumption	Port size	Dimensions HxWxL	Weight
13-01-003	DC driven Circulation Pumps with Brushless Motor	12V	51 l/min 808 GPH	47 l/min 745 GPH	80W	20 mm (3/4")	110x88x152 mm (4.3x3.5x6 in)	0.89 kg 2 lb
13-01-004		24V	61 l/min 967 GPH	57 l/min 903 GPH	120W			



albinus[®]

DC driven Circulation Pumps with Brushless Motor

DC driven Circulation Pumps with Brushless Motor